

# 2A30M

ex 1/S C

## SERRATURA DA APPLICARE SCREW-ON LOCK

SERIE  
2A

2A30M

1/S C

### FUNZIONAMENTO

Rotazione 360° (2 uscite chiave)

B

Rotazione 320° (1 uscita chiave)

N

Nichelato

OT

Ottonato

NE

Nero

BZ

Bronzato

### CILINDRO Ø 17

20

mm 20

22

mm 22

25

mm 25

30

mm 30

N

Cilindro numerato

### CIFRATURE

KD chiavi differenti

A

KA chiavi uguali

X

Gruppi di KA

M

Chiave maestra

### CHIAVI

Art.82 nichelata (2 pz)

PUNE

Art.82PU nero (2 pz)

PUG8

Art.82PU grigio (2 pz)

### FINITURE

14

US14 nichelato

OT

Ottonato

BZ

Bronzato

NE

Nero

### CATENACCI

Piano

P35

Piegato mm 3,5

P7

Piegato mm 7,5

P10

Piegato mm 10

P12

Piegato mm 12

P15

Piegato mm 15

### ACCESSORI

1 ghiera Art.401

7Z

1 controbordo Art.608

### CONFEZIONI

Commercio 20 pz

I

Industria 100 pz

1/S C

### OPERATION

Rotating 360° (2 key pull)

Rotating 320° (1 key pull)

### DIE CAST BODY

Nichel plated

Brass plated

Black

Bronze plated

### CILYNDER Ø 43/64"

25/32"

55/64"

63/64"

1 3/16"

Numbered cylinder

### KEY-CHANGES

KD keyed differently

KA keyed alike

KA in groups

Master key

### KEYS

Art.82 nickel plated (2 pcs)

Art.82PU black (2 pcs)

Art.82PU grey (2 pcs)

### FINISHES

US14 nickel plated

Brass plated

Bronze plated

Black

### BOLTS

Flat

Bent 9/64"

Bent 19/64"

Bent 25/64"

Bent 15/32"

Bent 19/32"

### ACCESSORIES

1 ring Art.401

1 striking plate Art.608

### PACKAGING

Boxed in 20's

Bulk in 100's

